

## SPECIFICATIONS

Power	100~240V AC 8.2V DC 6V1.2Ah Rechargeable Battery
Housing	SUS304 stainless steel
Display	1" 25mm red LED
Protection	IP54
Capacity	30/60/150/300/600 kg
Division	10/20/50/100/200 g
Units	kg/lb
Accuracy	Class III
Stable Time	≤8s
Zero Range	4% F.S.
Tare Rang	100%
Safety load	120% F.S.
Operating Temperature	-10 °C - 40 °C



## MODELS

Model	Part No.	Capacity	Division
CF30	630001	30kg	10g
CF60	630002	60kg	20g
CF150	630003	150kg	50g
CF300	630004	300kg	100g
CF600	630005	600kg	200g

## OPTIONAL

Accessories	Part No.
Bluetooth	690001
S.S hanging pan (for CF30)	690002
Aluminum suitcase	690003
S.S swivel hook	690004

## FUNCTIONS

Zero/Tare  
Hold  
Totalization  
Gravity value setting  
Power saving  
Auto zero  
Auto zero tracking

## FEATURES

- High quality alloy steel S-type load cell  
(Accuracy meets OIML Class III requirements)
- With remote control  
(Easy to operate)
- Fast response and stabilize
- Suitable for food industries, farm, warehouse, dock, factory, etc.