



## SPECIFICATIONS

|                       |                                                                         |
|-----------------------|-------------------------------------------------------------------------|
| Power                 | 5V USB Type-C Charger<br>3.7V4Ah Li-ion Battery<br>Optional 100-240V AC |
| Material              | Plastic/steel platform<br>SUS304 S.S. cover                             |
| Display               | FSTN 1.5" LCD                                                           |
| Capacity              | 50/100/200 kg                                                           |
| Division              | 2/5/10 g                                                                |
| Units                 | kg/lb                                                                   |
| Output                | RS232*1                                                                 |
| Load Cell             | Special sealed load cell module                                         |
| Load Cell Protection  | IP67                                                                    |
| Indicator Protection  | IP67                                                                    |
| Platform Size         | 300x400mm<br>400x500mm                                                  |
| Operating Temperature | -10 °C - 40 °C                                                          |



## FUNCTIONS

Counting  
Hold  
Classifying  
Animal weighing  
x10 accuracy  
APW  
Multi range selectable  
Linearity calibration selectable  
Multi communication protocols



## FEATURES

- K1C indicator with multi units and multi functions
- FSTN 1.5" LCD Display
- Default with RS232 interface
- Capacity up to 200kg
- High quality IP67 special sealed load cell module
- Four anti-slip adjusting feet
- Overload protection

## OPTIONAL

| Accessories          | Part No. |
|----------------------|----------|
| Bluetooth            | 109004   |
| Bluetooth-(With app) | 109005   |
| WiFi                 | 109007   |
| RS485                | 109008   |
| 4-20mA               | 109009   |
| USB                  | 109021   |

## MODELS

| Model   | Part No. | Size      | Capacity | Division | L.C.IP |
|---------|----------|-----------|----------|----------|--------|
| AGU3050 | 620269   | 300x400mm | 50kg     | 2g       | IP67   |
| AGU3100 | 620270   |           | 100kg    | 5g       |        |
| AGU4100 | 620271   | 400x500mm | 100kg    | 5g       |        |
| AGU4200 | 620272   |           | 200kg    | 10g      |        |

## DIMENSION / mm

| Model | a   | b   | h   | h1  | pack size   | G.W/kg | 1PC/CTN |
|-------|-----|-----|-----|-----|-------------|--------|---------|
| AGU3  | 300 | 400 | 160 | 500 | 810*380*225 | 14     | 1       |
| AGU4  | 400 | 500 | 160 | 600 | 910*480*230 | 20     | 1       |

