



## SPECIFICATIONS

Power	100-240V AC 12V DC adaptor Rechargeable battery
Material	Steel tube structure Stainless steel cover and pole
Display	38mm 1.5" LED
Capacity	15/30/60/150/300/600 kg
Division	5/10/20/50/100 g
Units	kg/lb
Output	RS232*1
Load Cell	M15/M17/M19
Load Cell Protection	IP65
Indicator Protection	IP54
Platform Size	400x500mm 500x600mm 600x800mm
Operating Temperature	-10 °C - 40 °C



## FUNCTIONS

Counting  
(Peak) Hold  
Totalization  
Animal weighing

## FEATURES

- X1 indicator with multi units and multi functions
- Large 38mm red LED display
- Default with RS232 interface
- Capacity up to 600kg
- High quality IP65 aluminum alloy load cell
- Four anti-slip adjusting feet
- Overload protection with Protecting fence

## OPTIONAL

Accessories	Part No.
S.S. bracket	109001
Relay 2 output	109002
Relay 4 output	109003
Bluetooth	109004
Bluetooth-(With app)	109005
Ethernet/WiFi	109006
WiFi	109007
RS485	109008
4-20mA	109009



## MODELS

Model	Part No.	Size	Capacity	Division	L.C.IP
ATK4030	620194	400x500mm	30kg	5g	IP65
ATK4060	620195	400x500mm	60kg	10g	
ATK4150	620196	400x500mm	150kg	20g	
ATK5060	620197	500x600mm	60kg	10g	
ATK5150	620198	500x600mm	150kg	20g	
ATK5300	620199	500x600mm	300kg	50g	
ATK6150	620200	600x800mm	150kg	20g	
ATK6300	620201	600x800mm	300kg	50g	
ATK6600	620202	600x800mm	600kg	100g	

## DIMENSION / mm

Model	a	b	h	h1	pack size	G.W/kg	1PC/CTN
ATK4*	400	500	125	615	895*515*175	18.5	1
ATK5*	500	600	130	620	995*615*200	31.5	1
ATK6*	600	800	150	690	1195*715*200	41.5	1

