



Single or Double Axle

Two platforms for choice
 - 0.9m or 2.2m width

Up to 30TON Capacity

Heavy duty design up to 30Ton/axle*
 * 3.2x2.2m platform

Epoxy Painting

Sand blasting + epoxy painting,
 Longer time for use



Pictures



Dynamic-Indicator



XM6

Specifications

POWER

120V/240V 50/60Hz
 Rechargeable battery 6V10Ah
 Estimated working: 40hrs

PLATFORM SIZE

3.2x0.9m / 3.2x2.2m

CAPACITY

20t | 30t

ACCURACY

± 1/1500 - static
 ± 1/100 - dynamic (≤5km/h)

NON-LINEARITY

<0.01%

TEMP. COEFFICIENT

5ppm/°C (F.S.)

UNIT

Kg/lb

OUTPUT

RS232
 USB
 WiFi (optional)
 Bluetooth (optional)

Description

PLATFORM

Class design with checked plate <
 Easy for installation and maintenance <
 Two platforms for choose <
 Suitable for single axle or double axle <
 Other platform size customized available*
 Epoxy painting for long time use <

LOAD CELL

OIML approved M36i column load cell <
 Stainless steel material <
 Hermetically sealed, IP68 <
 Optional HM9B load cell <

INDICATOR

8" Touch Screen <
 4 Cores ARM CPU <
 2GB memory with 4GB hard disk <
 Rugged ABS suitcase <
 Unlimited weighing records <
 Base on Windows CE 6.0* system <
 RS232, USB 2.0 output <
 Display of weight of each axle <
 Display of total truck weight <
 Excel, text or Database file output <
 Multi-languages support (default-English) <
 High speed thermal Printer <

Models

Part No.	410055	410056
Models	AXS3209	AXS3222
U.P.(USD)	US\$6,600.00	US\$9,000.00
Axle Capacity	20ton	30ton
Axle Type	Single	Double or more
Platform size	3.2 x 0.9m	3.2 x 2.2m