



TechnicalData

Power 100-240V 50/60Hz - 12V adaptor Rechargeable Battery: 6V4Ah Battery Life: 130 hours (no backlit)	Display LCD with backlight
Pan Dimensions BPH - 300 x 400mm BPHB - 400 x 500mm	Units Kg lb
Capacity 15 30 60 150 Kg	U.W. PLU 18 Memories
Division 5 10 20 50g	Sampling Speed 30times/second
Analog Input Signal 0.6mV/V - 3mV/V	Non-linearity ≤0.01%F.S.
Power Consumption 30mA - no backlit 65mA - with backlit	Approval CE
Operating Temperature -10°C - 40°C	RS232 Included



Features

- Big platform with s.s cover <
- Two platform sizes for selection <
- X7PC indicator with LCD display <
- RP58 high-speed thermal printer <
- Rechargeable 6V4A battery <
- Up to 130hrs operating time <
- Dual range capacity/division <
- Customer's display included <
- Zero and Tare function <
- 18 PLU keys (9 direct) <
- Accumulating function <
- Auto power saving setup <
- Multi-units exchange <
- Speed adjustable <
- Change function <
- Fixed value function <
- Price calculating per qty <
- Zero and full capacity tare <
- Accumulating function <
- Memory recall and clean <
- Gravity value setup <
- Auto power off <
- RS232 optional <
- WiFi optional <
- Bluetooth optional <
- Customized protocol optional <

* P58R - printer Models

Part No.	100906	100907	100908	100909	100910	100911	140066
Models	BPH15	BPH30	BPH60	BPH30B	BPH60B	BPH150B	P58R
U.P.(USD)	\$360.00	\$360.00	\$360.00	\$400.00	\$400.00	\$400.00	\$200.00
Capacity	15kg	30kg	60kg	30kg	60kg	150kg	-
Division	5g	10g	20g	10g	20g	50g	-
Pack Size	50 x 56 x 15cm		70 x 66 x 15cm				-
Weight	12kg		16kg				-