



*to be approved

VALUE EACH GRAM
HiWEIGH

BSD

SPECIFICATIONS

| | |
|-----------------------|---|
| Power | 5V USB Type-C Charger 3.7V4Ah Li-ion Battery Optional 100-240V AC |
| Material | Aluminum alloy structure SUS304 S.S. cover and pole |
| Display | FSTN 1.5" LCD |
| Capacity | 30/60/150/300 kg |
| Division | 2/5/10/20 g |
| Units | kg/lb |
| Output | RS232*1 |
| Load Cell | M17 |
| Load Cell Protection | IP65 |
| Indicator Protection | IP67 |
| Platform Size | 420x520mm |
| Operating Temperature | -10 °C - 40 °C |



FUNCTIONS

Counting
Hold
Classifying
Animal weighing
x10 accuracy
APW
Multi range selectable
Linearity calibration selectable
Multi communication protocols



FEATURES

- K1C indicator with multi units and multi functions
- FSTN 1.5" LCD Display
- Default with RS232 interface
- Capacity up to 300kg
- High quality IP65 aluminum alloy load cell
- Four anti-slip adjusting feet
- Overload protection

OPTIONAL

| Accessories | Part No. |
|----------------------|----------|
| Bluetooth | 109004 |
| Bluetooth-(With app) | 109005 |
| WiFi | 109007 |
| RS485 | 109008 |
| 4-20mA | 109009 |
| USB | 109021 |

MODELS

| Model | Part No. | Size | Capacity | Division | L.C.IP |
|---------|----------|-----------|----------|----------|--------|
| BSD4030 | 620221 | 450x520mm | 30kg | 2g | IP65 |
| BSD4060 | 620222 | | 60kg | 5g | |
| BSD4150 | 620223 | | 150kg | 10g | |
| BSD4300 | 620224 | | 60kg | 20g | |

DIMENSION / mm

| Model | a | b | h | h1 | pack size | G.W/kg | 1PC/CTN |
|-------|-----|-----|-----|-----|-------------|--------|---------|
| BSD4 | 520 | 420 | 130 | 600 | 910*560*190 | 19 | 1 |
| BSD4c | 520 | 420 | 130 | 600 | 910*560*190 | 19 | 1 |

