



## SPECIFICATIONS

Material	100-240V AC 6V2.8Ah Rechargeable Battery
Material	SUS304 S.S.
Display	Backlit FSTN LCD
Capacity	6/15/30/60/100 kg
Division	1/2/5/10/20 g
Units	kg   lb   g   oz
Output	2*RS232
Load Cell	M14i
Load Cell Protection	IP66
Indicator Protection	IP65
Platform Size	300x300mm 400x400mm
Operating Temperature	-10 °C - 40 °C



## FUNCTIONS

Zero/Tare  
Hold  
Counting  
Checkweigh  
Accumulation  
Animal weighing  
x10 accuracy

## OPTIONAL

Accessories	Part No.
Relay 4 output	109003
Bluetooth	109004
Bluetooth-(With app)	109005
Ethernet/WiFi	109006
WiFi	109007
4-20mA	109009

## FEATURES

- K7S indicator with multi units and multi functions
- 37mm backlit FSTN LCD display
- Default with double RS232 interface
- Accumulate up to 2000 records
- Capacity up to 100kg
- OIML/NTEP approved load cells
- Four anti-slip adjusting feet
- Anti-impact with buffering springs
- Overload protection



## MODELS

Model	Part No.	Size	Capacity	Division	L.C.IP
BSH3006	620253	300x300mm	6kg	1g	IP66
BSH3015	620254		15kg	2g	
BSH3030	620255		30kg	5g	
BSH4015	620256	400x400mm	15kg	2g	
BSH4030	620257		30kg	5g	
BSH4060	620258		60kg	10g	
BSH4100	620259		100kg	20g	

## DIMENSION / mm

Model	a	b	h	h1	pack size	G.W/kg	1PC/CTN
BSH3	300	300	100	480	795*515*160	6	1
BSH4	400	400	100	480	560*460*220	8	1

