



*to be approved

SPECIFICATIONS

Power	5V USB Type-C Charger 3.7V4Ah Li-ion Battery Optional 100-240V AC
Material	Aluminum alloy structure SUS304 S.S. cover and pole
Display	FSTN 1.5" LCD
Capacity	30/60/150/300/500 kg
Division	2/5/10/20/50 g
Units	kg/lb
Output	RS232*1
Load Cell	M15/M17
Load Cell Protection	IP65
Indicator Protection	IP67
Platform Size	300x400mm 400x500mm 450x600mm
Operating Temperature	-10 °C - 40 °C



FUNCTIONS

Counting
Hold
Classifying
Animal weighing
x10 accuracy
APW
Multi range selectable
Linearity calibration selectable
Multi communication protocols



FEATURES

- K1C indicator with multi units and multi functions
- FSTN 1.5" LCD Display
- Default with RS232 interface
- Capacity up to 500kg
- High quality IP65 aluminum alloy load cell
- Four anti-slip adjusting feet
- Overload protection

OPTIONAL

Accessories	Part No.
Bluetooth	109004
Bluetooth-(With app)	109005
WiFi	109007
RS485	109008
4-20mA	109009
USB	109021

MODELS

Model	Part No.	Size	Capacity	Division	L.C.IP
BSK3030	620212	300x400mm	30kg	2g	IP65
BSK3060	620213	300x400mm	60kg	5g	
BSK3150	620214	300x400mm	150kg	10g	
BSK4060	620215	400x500mm	60kg	5g	
BSK4150	620216	400x500mm	150kg	10g	
BSK4300	620217	400x500mm	300kg	20g	
BSK5150	620218	450x600mm	150kg	10g	
BSK5300	620219	450x600mm	300kg	20g	
BSK5500	620220	450x600mm	500kg	50g	

DIMENSION / mm

Model	a	b	h	h1	pack size	G.W/kg	1PC/CTN
BSK3	300	400	110	545	450*370*180	6.5	1
BSK45	400	500	130	510	560*470*215	12	1
BSK46	450	600	130	490	650*520*215	16	1

