

SPECIFICATIONS

Power	100-240V AC 6V2.8Ah Rechargeable Battery
Material	SUS304 S.S.
Display	Backlit FSTN LCD
Capacity	6/15/30/60/150/200/300/500 kg
Division	1/2/5/10/20/50/100 g
Units	kg lb g oz
Output	2*RS232
Load Cell	M14i/M17P
Load Cell Protection	IP66/IP68&IP69K
Indicator Protection	IP65
Platform Size	300x300mm 300x400mm 400x400mm 400x500mm 500x600mm 600x600mm
Operating Temperature	-10 °C - 40 °C



FUNCTIONS

Zero/Tare
Hold
Counting
Checkweigh
Accumulation
Animal weighing
x10 accuracy

FEATURES

- K7S indicator with multi units and multi functions
- 37mm backlit FSTN LCD display
- Default with double RS232 interface
- Accumulate up to 2000 records
- Capacity up to 500kg
- OIML/NTEP approved load cells
- M*SC load cell shields
(Waterproof, insect-proof or anti-rodent)
- Four anti-slip adjusting feet
- Rubber buffer pan supports
- Overload protection

OPTIONAL

Accessories	Part No.
Relay 4 output	109003
Bluetooth	109004
Bluetooth-(With app)	109005
Ethernet/WiFi	109006
WiFi	109007
4-20mA	109009



MODELS

Model	Part No.	Size	Capacity	Division	L.C.IP	
BSS3006	620230	300x300mm	6kg	1g	IP66	
BSS3015	620231		15kg	2g		
BSS3030	620232		30kg	5g		
BSS3030L	620233	300x400mm	30kg	5g		
BSS3060L	620234		60kg	10g		
BSS3150L	620235		150kg	20g		
BSS4030	620236	400x400mm	30kg	5g	IP68&IP69K	
BSS4060	620237		60kg	10g		
BSS4150	620238		150kg	20g		
BSS4060L	620239	400x500mm	60kg	10g		
BSS4150L	620240		150kg	20g		
BSS4200L	620241		200kg	20g		
BSS5060	620242	500x600mm	60kg	10g	IP68&IP69K	
BSS5150	620243		15kg	20g		
BSS5300	620244		300kg	50g		
BSS6150	620245	600x600mm	150kg	20g		IP68&IP69K
BSS6300	620246		300kg	50g		
BSS6500	620247		500kg	100g		

DIMENSION / mm

Model	a	b	h	h1	pack size	G.W/kg	1PC/CTN
BSS33	300	300	120	350	695*415*160	13	1
BSS34	300	400	120	450	795*415*160	15	1
BSS44	400	400	145	450	795*515*160	17	1
BSS45	400	500	145	550	895*515*160	20	1
BSS56	500	600	155	650	995*615*175	27	1
BSS66	600	600	155	650	995*715*175	32	1

