


SPECIFICATIONS

Power	10V DC Adaptor 6V4Ah Rechargeable Battery
Display	LCD display with backlight
Capacity	3/6/15/30 kg
Division	0.1/0.2/0.5/1 g
Units	kg/lb
Accuracy	Class III
A/D Rate	20 times/second
Non-linearity	≤0.01%F.S.
Pan Size	310x220mm
Display Resolution	1/30,000
Operating Temperature	-10 °C - 40 °C



FEATURES

- 3 backlit LCD displays
- Bubble level and 4 adjustable feet
- Dust cover blister, easy to clean
- Optional RS232 or Bluetooth
- APW/Auto average weight recalculate
Minimize the counting error, make the counting result more accurate!

FUNCTIONS

- Counting
- Accumulate
- 20 PLU (10 direct operation)
- Full capacity tare
- Record recall and clean
- Adjustable weighing speed

PACK SIZE

820*400*310mm (4pcs)

WEIGHT

16kg(4pcs)



MODELS

Model	Part No.	Capacity	Division
CCX3	641013	3kg	0.1g
CCX6	641014	6kg	0.2g
CCX15	641015	15kg	0.5g
CCX30	641016	30kg	1g

OPTIONAL

Accessories	Part No.
RS232	109009
Bluetooth	109017