

SPECIFICATIONS

Power	100V or 220V AC 9V DC 6V5Ah Rechargeable Battery
Housing	Aluminum alloy
Display	1.2" 30mm red LED
Protection	IP53
Capacity	1/3/5/10/15/20 t
Division	0.5/1/2/5/10 kg
Units	kg/lb/N
Accuracy	Class III
Stable Time	≤10s
Zero Range	4% F.S.
Tare Rang	100% F.S.
Safety load	125% F.S.
Ultimate load	400% F.S.
Operating Temperature	-20 °C - 50 °C



MODELS

Model	Part No.	Capacity	Division
CSB1K	630010	1000kg	0.5kg
CSB3K	630011	3000kg	1kg
CSB5K	630012	5000kg	2kg
CSB10K	630013	10000kg	5kg
CSB15K	630014	15000kg	5kg
CSB20K	630015	20000kg	10kg

OPTIONAL

Accessories	Part No.
Bluetooth	690001
E380 palm indicator	690005
E580 palm indicator	690006
MDS3 wireless display	690007
High-temperature protecting plate	690008

FUNCTIONS

Zero/Tare
Hold
Totalization
Power saving
Auto zero
Auto zero tracking
Gravity compensation

FEATURES

- Large capacity up to 20000kg
- High quality alloy steel S-type load cell (Accuracy meets OIML Class III requirements)
- Remote control, remote distance <15m (Easy to operate)
- Galvanized shackle with safe lock
- Fast response and stabilize
- Overload warning