

## SPECIFICATIONS

Power	3 x AA Batteries
Housing	Aluminum alloy--till 5000kg Alloy Steel--over 5000kg
Display	1.2" 30mm backlight LCD
Protection	IP54
Capacity	1/2/3/5/10/20/30/50/100/200t
Division	0.5/1/2/5/10/20/50/100 kg
Units	kg/t/lb/klb/N/kN
Accuracy	Class III
Stable Time	≤10s
Zero Range	4% F.S.
Tare Rang	20% F.S.
Safety load	125% F.S.
Ultimate load	400% F.S.
Operating Temperature	-10 °C - 40 °C



## MODELS

Model	Part No.	Capacity	Division
CSD1K	630016	1000kg	0.5kg
CSD3K	630017	3000kg	1kg
CSD5K	630018	5000kg	2kg
CSD10K	630019	10000kg	5kg
CSD20K	630020	20000kg	10kg
CSD30K	630021	30000kg	10kg
CSD50K	630022	50000kg	20kg
CSD100K	630023	100000kg	50kg
CSD200K	630024	200000kg	100kg

## OPTIONAL

Accessories	Part No.
E380 palm indicator	690005
E580 palm indicator	690006
MDS3 wireless display	690007

## FUNCTIONS

Zero/Tare  
Peak Hold  
Totalization  
Power saving  
Auto zero  
Auto zero tracking  
Record search and clean

## FEATURES

- Large capacity up to 200000kg
- Bright LCD display with backlight
- High quality alloy steel S-type load cell  
(Accuracy meets OIML Class III requirements)
- Remote control, remote distance >15m  
(Easy to operate)
- Fast response and stabilize
- Two setpoints for weight limit
- Calibration with remote control
- Overload warning