

## SPECIFICATIONS

Power	100V or 220V AC 9V DC 6V5 Ah Rechargeable Battery
Housing	Aluminum alloy
Display	1.2" 30mm red LED
Protection	IP53
Capacity	100/300/500/1000 kg
Division	50/100/200/500 g
Units	kg/lb/N
Accuracy	Class III
Stable Time	≤10s
Zero Range	4% F.S.
Tare Rang	100% F.S.
Safety load	120% F.S.
Ultimate load	400% F.S.
Operating Temperature	-20 °C - 50 °C



## MODELS

Model	Part No.	Capacity	Division
CSE100	630006	100kg	50g
CSE300	630007	300kg	100g
CSE500	630008	500kg	200g
CSE1000	630009	1000kg	500g

## OPTIONAL

Accessories	Part No.
Bluetooth	690001
E380 palm indicator	690005
E580 palm indicator	690006
MDS3 wireless display	690007

## FUNCTIONS

Zero/Tare  
Hold  
Totalization  
Record search and clean  
Power saving  
Auto zero  
Auto zero tracking

## FEATURES

- Large capacity up to 1000kg
- High quality alloy steel S-type load cell (Accuracy meets OIML Class III requirements)
- Remote control, remote distance >15m (Easy to operate)
- Galvanized shackle with safe lock
- Galvanized 360° swivel hook
- Fast response and stabilize