



### 10.2" TFT TouchDisplay

Friendly-design TFT display  
Sensitive touch operation  
Memory of 100 formulas  
Check data at any time:  
Target value, the upper/lower limit  
the qualified or unqualified number  
Self-learning and self-checking function  
USB interface for the weighing data output  
Can be connected to labelling machine, barcode  
reader, metal detector or other peripheral equipments  
3-class password protection, and multi statistics function

### SUS304 StainlessSteel

Completely stainless steel structure  
Suitable for food, pharmacy industries  
optional IP67 protection - for seafood/slaughtering industries  
High precision load cell made by HBM or equivalent  
Brushless DC motor, European or Taiwan brand  
High quality Habasit transport belt  
Different rejecting system for selection  
Modular design, easy for installation, cleaning  
optional SUS316 material

**Capacity**  
300g - 60kg

**Division**  
0.05g - 10g

**Display**  
10.2" TFT

**Protection**  
IP54  
IP67 (optional)

**Belt Width**  
100mm - 650mm

**Operating Temperature**  
0 - 40°C

*\*All those product names, logos, brands and other trademarks featured or referred to within this catalog are the property of their respective trademark holders.*

**Power**  
110V or 220V 50Hz  
single phase


**Load Cell**  
HBM\* or equivalent

**Motor**  
STS\*

**Belt**  
Habasit\*

**Inverter**  
Delta\*

**Relay**  
Omron\*



Air Blast

For light items, like instant noodles, tea/coffee pouches, paper roll, small hardwares, etc.



Flip Bar

For items a little heavy but not easy break, such as meat, fish, canned food, etc.




Pusher

For heavy items, like beverage packs, milk boxes, hardware boxes, etc.




Drop Flap

For thin items with not so fast speed, like glass noodles, snacks, etc.



Rising

For thin items but need fast speed, such as face pack, spice pouches, etc.



Belt Type

For big packages, like woven bags, kraft paper bags, etc.

**RejectingSystem**

**Models**

**Value Each Gram**

\* e - Economical Models | \* none - Standard Models

\* h - High class models | \* i - Intelligent Models

\* Intelligent models with function of self-learning, interfaces to barcode reader, ink jet coding system, DCS, traceable system, labelling system, etc.



Part No.	210001	210002	210003	210004		210005	210006	210007	210008	
Models	CW300e	CW300	CW300h	CW300i	unit	CW600e	CW600	CW600h	CW600i	
Capacity	300g						600g			
Check Range	10 - 300g						10 - 600g			
Division	0.2	0.1	0.05	0.05	g	0.2	0.1	0.05	0.05	
Accuracy	±1	±0.3	±0.15	±0.15	g	±1	±0.3	±0.15	±0.15	
Max.Speed	300	200	120	150	pcs/minute	220	150	120	140	
Conveyor Speed	96	70	45	55	meter/minute	96	70	45	55	
Package Length	50-200					mm	50-300			
Package Width	30-120					mm	30-180			
Package Height	2-100					mm	2-150			
Weigh Zone	Length - 180   320 Width - 100   160					mm	Length - 320   400 Width - 160   240			
Product Memory	100					groups	100			
Display	7" TFT	10.2" TFT				7" TFT	10.2" TFT			
Power	110V or 220V 50Hz						110V or 220V 50Hz			
Protection	IP54 (optional IP67)						IP54 (optional IP67)			

Part No.	210009	210010	210011	210012		210013	210014	210015	210016	
Models	CW1200e	CW1200	CW1200h	CW1200i	unit	CW3000e	CW3000	CW3000h	CW3000i	
Capacity	1200g						3000g			
Check Range	10 - 1200g						30 - 3000g			
Division	0.5	0.2	0.1	0.1	g	1	0.5	0.2	0.2	
Accuracy	±1.5	±0.6	±0.3	±0.3	g	±3	±1.5	±0.6	±0.6	
Max.Speed	300	200	120	150	pcs/minute	160	120	80	95	
Conveyor Speed	96	70	45	55	meter/minute	96	70	45	55	
Package Length	50-350					mm	50-380			
Package Width	30-220					mm	30-250			
Package Height	2-180					mm	2-200			
Weigh Zone	Length - 400   450 Width - 240   300					mm	Length - 500 Width - 300			
Product Memory	100					groups	100			
Display	7" TFT	10.2" TFT				7" TFT	10.2" TFT			
Power	110V or 220V 50Hz						110V or 220V 50Hz			
Protection	IP54 (optional IP67)						IP54 (optional IP67)			

Part No.	210017	210018	210019	210020		210021	210022	210023	210024	
Models	CW6000e	CW6000	CW6000h	CW6000i	unit	CW15Ke	CW15K	CW15Kh	CW15Ki	
Capacity	6000g						15kg			
Check Range	60 - 6000g						150g - 15kg			
Division	1	0.5	0.2	0.2	g	2	1	0.5	0.5	
Accuracy	±3	±1.5	±0.6	±0.6	g	±6	±3	±1.5	±1.5	
Max.Speed	100	80	65	75	pcs/minute	85	80	65	78	
Conveyor Speed	60	50	40	45	meter/minute	60	55	45	55	
Package Length	50-400					mm	50-450			
Package Width	30-280					mm	30-320			
Package Height	2-250					mm	2-280			
Weigh Zone	Length - 550 Width - 350					mm	Length - 600 Width - 400			
Product Memory	100					groups	100			
Display	7" TFT	10.2" TFT				7" TFT	10.2" TFT			
Power	110V or 220V 50Hz						110V or 220V 50Hz			
Protection	IP54 (optional IP67)						IP54 (optional IP67)			

Part No.	210025	210026	210027	210028		210029	210030	210031	210032	
Models	CW30Ke	CW30K	CW30Kh	CW30Ki	unit	CW60Ke	CW60K	CW60Kh	CW60Ki	
Capacity	30kg						60kg			
Check Range	300g - 30kg						600g - 60kg			
Division	2	1	0.5	0.5	g	10	5	2	2	
Accuracy	±6	±3	±1.5	±1.5	g	±30	±15	±6	±6	
Max.Speed	85	80	65	78	pcs/minute	60	60	50	55	
Conveyor Speed	50	50	45	55	meter/minute	50	50	45	55	
Package Length	50-800					mm	50-800			
Package Width	30-320					mm	30-320			
Package Height	2-280					mm	2-280			
Weigh Zone	Length - 600   800 Width - 400   500					mm	Length - 800   1100 Width - 500   650			
Product Memory	100					groups	100			
Display	7" TFT	10.2" TFT				7" TFT	10.2" TFT			
Power	110V or 220V 50Hz						110V or 220V 50Hz			
Protection	IP54 (optional IP67)						IP54 (optional IP67)			