

SPECIFICATIONS

Power	3 x AA Batteries Optional rechargeable battery--CXS
Housing	Aluminum alloy
Display	0.7" 17.8mm backlight LCD--CX 0.8" 20mm backlight LCD--CXS
Protection	IP53
Capacity	50/60/100/200/300 kg
Division	20/50/100 g
Units	kg/lb/N--CX kg/lb--CXS
Accuracy	Class III
Stable Time	≤10s
Zero Range	4% F.S.
Tare Rang	100% F.S.
Safety load	120% F.S.
Ultimate load	300% F.S.
Operating Temperature	-10 °C - 40 °C



MODELS

Model	Part No.	Capacity	Division
CX60	630025	60kg	20g
CX100	630026	100kg	50g
CX200	630027	200kg	100g
CX300	630028	300kg	100g
CXS50	630029	50kg	20g
CXS100	630030	100kg	50g
CXS200	630031	200kg	100g
CXS300	630032	300kg	100g

OPTIONAL

Accessories	Part No.
Bluetooth (CXS)	690001

FUNCTIONS

Zero/Tare
Hold
Power saving
Auto zero
Zero tracking

FEATURES

- Bright LCD display with backlight
- Stainless steel shackle and hook
- Fast response and stabilize