



400*400mm Platform

SUS304 stainless steel cover
400 x 400mm rugged platform
Buffering rubber pads under cover
Anti-slip rubber mat on the cover
Indicator tower indicator arm
Aluminum height rod
Plastic power coated
OIML M15 load cell

X2-BMI Indicator

ABS housing
Stainless steel bracket
LCD display with backlight
BMI check function
Hold function
Kg/lb units exchange
G value (gravity) adjusting
Optional RS232 interface
Optional Bluetooth output

X3AM Indicator

ABS housing
OIML approved
Stainless steel bracket
LCD display with backlight
Zero/Tare function
Kg/lb units exchange
Default with RS232 interface
Optional Bluetooth output



TechnicalData HE

Power 100-240V - 10V adaptor Battery: 6V1.2Ah Battery life: 24hr	Display LCD - 23mm
Capacity 200kg	Units Kg lb g oz
Accuracy 50g	Output RS232 (optional)
Height Rod 200cm	Operating Temperature -10°C - 40°C
Height Accuracy 1mm	Approval CE

TechnicalData HEM

Power 100-240V - 12V adaptor Battery: 6V2.8Ah Battery life: 30hr	Display LCD - 25mm
Capacity 200kg	Units Kg lb
Accuracy 50g	Output RS232
Height Rod 200cm	Operating Temperature -10°C - 40°C
Height Accuracy 1mm	Approval OIML/EC Type T8127 (NMI) CE

Models

Part No.	101003	101004
Models	HE	HEM
U.P.(USD)	\$460.00	\$552.00
Capacity	200kg	200kg
Division	50g	50g
Pack Size	65 x 45 x 20cm	65 x 45 x 20cm
Weight	18kg	18kg