



SPECIFICATIONS

Material	100-240V AC 9-24V DC 6V1.2Ah / 7.4V6.8Ah Rechargeable Battery
Material	SUS316 S.S.
Display	Backlit FSTN LCD
Capacity	6/15/30/60/150 kg
Division	1/2/5/10/20 g
Units	kg lb g oz
Output	RS232*2
Load Cell	M13P/M15P/M17P
Load Cell Protection	IP68 & IP69K
Indicator Protection	IP68 & IP69K
Platform Size	300x300mm 400x400mm 400x500mm
Operating Temperature	-10 °C - 40 °C



FUNCTIONS

Hold
Checkweigh
Animal weighing
Counting
x10 accuracy
Shortcut keys settings
Continuous and stable output
Multi communication protocols

FEATURES

- K9 indicator with multi units and multi functions
- Big backlit FSTN LCD display
- Default with double RS232 interface
- Washdown design, OIML NTEP IP68 & IP69K load cell (Easy and safe to clean with water)
- Capacity up to 150kg
- Four anti-slip S.S. adjusting feet
- Silicon buffer pan supports
- Overload protection
- Provide customized platform size
- Perfectly meet the weighing needs of the food, pharmaceutical and other industries.

OPTIONAL

Accessories	Part No.
WiFi	109007
Bluetooth	109016
USB	109017
Alarming light	109019
Pedal or mechanical switch	109020



MODELS

Model	Part No.	Size	Capacity	Division	L.C.IP
K9T3006	620260	300x300mm	6kg	1g	IP68 & IP69K
K9T3015	620261		15kg	2g	
K9T3030	620262		30kg	5g	
K9T4030	620263	400x400mm	30kg	5g	
K9T4060	620264		60kg	10g	
K9T4150	620265		150kg	20g	
K9T5030	620266	400x500mm	30kg	5g	
K9T5060	620267		60kg	10g	
K9T5150	620268		150kg	20g	

DIMENSION / mm

Model	a	b	h	h1	pack size	G.W/kg	1PC/CTN
K9T3	300	300	150	600	695*415*160	11.5	1
K9T4	400	400	162	620	795*415*160	17.5	1

