



SPECIFICATIONS

Power	5V USB Type-C Charger 3.7V4Ah Li-ion Battery Optional 100-240V AC
Material	Aluminum structure Stainless steel cover
Display	FSTN 1.5" LCD
Capacity	6/15/30/60/150 kg
Division	1/2/5/10/20 g
Units	kg/lb
Output	RS232*1
Load Cell	M17
Load Cell Protection	IP65
Indicator Protection	IP67
Platform Size	280x380mm
Operating Temperature	-10 °C - 40 °C



FUNCTIONS

Counting
Hold
Classifying
Animal weighing
x10 accuracy
APW
Multi range selectable
Linearity calibration selectable
Multi communication protocols

FEATURES

- K1C indicator with multi units and multi functions
- FSTN 1.5" LCD Display
- Default with RS232 interface
- Capacity up to 150kg
- High quality IP65 aluminum alloy load cell
- Portable design with handle
- Four anti-slip adjusting feet
- Overload protection

OPTIONAL

Accessories	Part No.
Bluetooth	109004
Bluetooth-(With app)	109005
WiFi	109007
RS485	109008
4-20mA	109009
USB	109021



MODELS

Model	Part No.	Size	Capacity	Division	L.C.IP
LOG3006	620225	280x380mm	6kg	1g	IP65
LOG3015	620226		15kg	2g	
LOG3030	620227		30kg	5g	
LOG3060	620228		60kg	10g	
LOG3150	620229		150kg	20g	

DIMENSION / mm

Model	a	b	h	pack size	G.W/kg	1PC/CTN
LOG	280	380	130	575*425*160	17	1

