

### SPECIFICATIONS

Capacity 5-50kg	Sensitivity 2.0±0.2mV/V	Creep (10 Min) 0.015% F.S.	Input Resistance 409±6Ω
Material Aluminum alloy	Overload Limitation 150% F.S.	Zero Output ±2% Emax	Non-linearity ±0.017% Emax.
Protection IP65	Output Resistance 350±3Ω	Temperature Effect Zero 0.17% F.S. / 10°C	Non-Repeatability ±0.01% Emax.
Accuracy C3	Insulation Resistance ≥5000mΩ (50V)	Temperature Effect Sensitivity 0.014% F.S. / 10°C	Recommended Excitation 5-12VDC
			Operating Temperature -35-65°C

### FEATURES



- M13-CE
- M13M-OIML/NTEP
- Capacity up to 50kg
- Aluminum alloy material
- Default cable length is 0.4m, diameter is 3.9mm  
(Optional customized longer cable)
- Recommended platform: from 200\*200mm to 300\*300mm
- Interchangeable with below models:  
HMB\* PW6C, Mettler Toledo\* MT1022,  
Tedeo-Huntleigh\* 1022, Zemic\* L6D, Flintec\* PC22



### MODELS

Part No.	120001	120002	120003	120004	120005	120006	120007
M13	5kg	10kg	20kg	30kg	35kg	40kg	50kg
Part No.	120008	120009	120010	120011	120012	120013	120014
M13M	5kg	10kg	20kg	30kg	35kg	40kg	50kg
Class	C3						
IP	IP65						

### DIMENSION / mm



Weight: 0.2kg