

SPECIFICATIONS

Power	12V DC Adaptor 6V4Ah Rechargeable Battery
Display	LCD display with backlight
Capacity	3/6/15/30 kg
Division	1/2/5/10 g
Units	kg/g/lb
Accuracy	Class III
A/D Rate	20 times/second
Non-linearity	≤0.01%F.S.
Pan Size	315x250mm
Display Resolution	1/3,000(approval)--1/30,000
Operating Temperature	-10 °C - 40 °C



VALUE EACH GRAM
HiWEIGH
PC5



FUNCTIONS

- Price computing
- 20 PLU (10 direct operation)
- Money-change
- Full capacity tare
- Accumulate
- Record recall and clean
- Fixed value
- Gravity value setting

MODELS

Model	Part No.	Capacity	Division
PC515	642005	6/15kg	2/5g
PC530	642006	15/30kg	5/10g
PC515H	642007	6/15kg	2/5g
PC530H	642008	15/30kg	5/10g
PC515M	642009	6/15kg	2/5g
PC530M	642010	15/30kg	5/10g
PC515HM	642011	6/15kg	2/5g
PC530HM	642012	15/30kg	5/10g

OPTIONAL

Accessories	Part No.
RS232	109009
Bluetooth	109017

FEATURES

- OIML and EU Type approval, legal for trade
- 3 backlit LCD displays
- Dual ranges capacity
- Double aluminum load cell supporter
- Bubble level and 4 adjustable feet
- Dust cover blister, easy to clean
- PC5*H(M) with pole display
- Accumulate up to 20 items
Accumulate by quantity up to 99 items
- TISA, Delta or customizable protocol for cash register



PACK SIZE

820*400*310mm (4pcs)

WEIGHT

16kg(4pcs)