

## SPECIFICATIONS

Power	12V DC Adaptor 6V4Ah Rechargeable Battery
Display	LCD display with backlight
Capacity	3/6/15/30 kg
Division	1/2/5/10 g
Units	kg/g/lb
Accuracy	Class III
A/D Rate	20 times/second
Non-linearity	≤0.01%F.S.
Pan Size	315x250mm
Display	1/3,000(approval)--1/30,000
Resolution	
Operating Temperature	-10 °C - 40 °C



## MODELS

Model	Part No.	Capacity	Division
PC615	642013	6/15kg	2/5g
PC630	642014	15/30kg	5/10g
PC615H	642015	6/15kg	2/5g
PC630H	642016	15/30kg	5/10g
PC615M	642017	6/15kg	2/5g
PC630M	642018	15/30kg	5/10g
PC615HM	642019	6/15kg	2/5g
PC630HM	642020	15/30kg	5/10g

## OPTIONAL

Accessories	Part No.
RS232	109009
Bluetooth	109017

VALUE EACH GRAM  
**HiWEIGH**  
PC6



## FUNCTIONS

Price computing  
40 PLU (20 direct operation)  
Money-change  
Full capacity tare  
Accumulate  
Record recall and clean  
Fixed value  
Gravity value setting

## FEATURES

- OIML and EU Type approval, legal for trade
- One large backlit LCD display
- Dual ranges capacity
- Double aluminum load cell supporter
- Bubble level and 4 adjustable feet
- Dust cover blister, easy to clean
- PC6\*H(M) with pole display
- Accumulate up to 20 items  
Accumulate by quantity up to 99 items
- TISA, Delta or customizable protocol for cash register



PACK SIZE

820\*400\*310mm (4pcs)

WEIGHT

16kg(4pcs)