



Technical Data

Power

100-240V - 12V1A adaptor
 Rechargeable Battery: 6V4Ah
 Estimated working time:
 130hrs - no backlit
 60hrs - with backlit

Pan Dimensions

315 x 250mm

Capacity

3 | 6 | 15 | 30Kg

Display Resolution

1/3,000

Net Weight

6Kg

Display

LCD with backlit

Units

Kg | lb | g | oz, etc.

Sampling Speed

20 times/second

Non-linearity

≤0.01%F.S.

Power Consumption

30mA - no backlit
 65mA - with backlit
 77mA - with backlit | RS232

PLU

40 (20 direct)

Operating Temperature

-10°C - 40°C
 ≤80% non-condensing

Storage Temperature

-25°C - 55°C
 ≤80% non-condensing

Approval

CE
 EC Type (pending)

RS232

Optional

Features

- Stainless steel housing <
- Big s.s pan 315 x 250mm <
- Aluminum load cell supporter <
- Big LCD display with backlit <
- Rechargeable 6V battery <
- 130hrs operating time (no backlit) <
- Dual range capacity <
- 3-window rear display <
- 40 PLU (20 direct) keys <
- Multi-units for selection <
- Money-change function <
- Fixed value function <
- Price calculating per qty <
- Zero and full capacity tare <
- Accumulating function <
- Memory recall and clean <
- Gravity value setup <
- Auto power off <
- RS232 optional <
- WiFi optional <
- Bluetooth optional <
- Customized protocol optional <

Models

Part No.	100878	100879	100880	100881
Models	PC6S15	PC6S30	PC6S15M	PC6S30M
U.P.(USD)	\$260.00	\$260.00	\$300.00	\$300.00
Capacity	6/15kg	15/30kg	6/15kg	15/30kg
Division	2/5g	5/10g	2/5g	5/10g
Pack Size	78 x 45 x 35cm (4pcs)			
Weight	26kg (4pcs)			