



double display



remote control

Value Each Gram A professional weighing products manufacturer and supplier

Features

- > Double LCD display with backlight
- > Operating by remote control
- > Stainless steel hook and pan
- > Rechargeable 6V3.2Ah battery
- > Capacity of 15kg and 30kg
- > OIML R60 Class III accuracy
- > Kg | lb unit exchange
- > Zero and full capacity tare
- > Accumulating function
- > Auto power off

Technical Data

Power

SCALE
110V/220V - 9V500mA Adaptor
Rechargeable Battery: 6V3.2Ah
Charge time: 12hrs
Estimated working time:
130hrs - no backlight
26hrs - backlight level3, no standby
14hrs - backlight level5, no standby

Remote Control: 3xAAA

Capacity

15 | 30Kg

Display Resolution

1/3,000

Net Weight

3.1kg

Display

LCD (22mm)

Units

Kg | lb

Safety Load

120%F.S.

Ultimate Load

400%F.S.
(not include pan)

Overload

100%F.S. + 9e

Stable Time

≤10s

Operating Temperature

-10°C - 40°C
≤80% non-condensing

Storage Temperature

-25°C - 55°C
≤80% non-condensing

Approval

CE

Models

Part No.	100904	100905
Models	PCX15	PCX30
U.P.(USD)	\$328.00	\$328.00
Capacity	15kg	30kg
Division	5g	10g
Pack Size	37 x 37 x 20cm	
Weight	4.5kg	