



SPECIFICATIONS

Power	100-240V AC 6V Rechargeable Battery
Housing	Carbon steel--PHA SUS304 S.S.--PHAS
Display	Backlit FSTN LCD
Capacity	2000kg
Division	0.5kg
Units	kg/lb
Accuracy	Class III
Output	2*RS232
Load Cell	M28/M28S
Load Cell Protection	IP67
Platform Size	1150x540mm 1220x680mm
Operating Temperature	-10 °C - 40 °C

FEATURES

- K7S indicator with multi units and multi functions
- 37mm backlit FSTN LCD display
- Accumulate up to 2000 records
- PHAS made with SUS304 S.S.
- Four high-quality IP67 shear beam load cells
- 540mm or 680mm for different market
- Optional 2,500kg/5,000lb or 3,000kg/6,000lb
- Optional thermal printer

MODELS

Model	Part No.	Size	Capacity	Division
PHA	622105	1150x540mm	2,000kg	0.5kg
PHA680	622106	1220x680mm		
PHAS	622107	1150x540mm	2,000kg	0.5kg
PHAS680	622108	1220x680mm		

FUNCTIONS

Zero/Tare
Hold
Counting
Checkweigh
Accumulation
Animal weighing
x10 accuracy

OPTIONAL

Accessories	Part No.
Relay 4 output	109003
Bluetooth	109004
Bluetooth-(With app)	109005
Ethernet/WiFi	109006
WiFi	109007
4-20mA	109009