

Options

MDS | MDSS remote display

K3000

Indicator/load-cell

M36i

Specifications

POWER 100-240V (50-60Hz)

PLATFORM SIZE

Width - 3m or 3.4m Length - 16 to 24m

CAPACITY

80t - 120t

ACCURACY 20kg

UNITS

Kg, t

OUTPUT

RS232 RS485

RJ45 (optional) SD card (optional)

COMMUNICATION

Continuous Modbus-RTU

Modbus-TCF Ethernet - optional

Description

PLATFORM

Structure designed with H beams < Modules design for container/truck load < Width of 3m or 3.4m option < Length from 16m to 24m* <

Modbus OIML (E

Big side guide of H beams 500x200 < * other length customized demand * concrete not included in the shipping list

LOAD CELL

OIML approved M36i column load cell < Stainless steel material < Hermetically sealed, IP68 < Optional HM9B load cell <

INDICATOR

S.S housing, IP65 protection < 240x128 dot matrix LCD <

High accuracy up to 10,000e < Anti-vibration and anti-surge design <

Easy to operation with big LCD display < Multi interface: RS232, RS485, Ethernet, etc. < Super anti-interference technology: <

Analog or digital working mode <

Print

Models

				Models
Part No.	410031	410032	410033	410034
Models	TCH316	TCH318	TCH321	TCH324
Capacity	80Ton	100Ton	100Ton	120Ton
Division	20kg	20kg	20kg	20kg
Platform size	3x16m	3x18m	3x21m	3x24m
Part No.	410035	410036	410037	410038
Models	TCH3416	TCH3418	TCH3421	TCH3424
Capacity	80Ton	100Ton	100Ton	120Ton
Division	20kg	20kg	20kg	20kg
Platform size	3.4x16m	3.4x18m	3.4x21m	3.4x24m