

Value Each Gram

**HiWEIGH**  
Weighing system & solution

A professional weighing products manufacturer and supplier

## Hydraulic Wheels

Moveable design with hydraulic wheels  
Easy to move by two men

## Double Deck

No need special foundation  
Easy to weigh at any place, any time



Modbus

## Description

### PLATFORM

- > Double deck design with checked plate
- > With hydraulic wheels, easy to move
- > Double ramps included
- > Width of 3m (2.5m optional)
- > Length of 6m or 9m
- > Epoxy painting for long time use

### LOAD CELL

- > OIML approved M36i column load cell
- > Stainless steel material
- > Hermetically sealed, IP68
- > HM9B load cell optional

### INDICATOR

- > S.S housing with IP65 protection
- > 240x128 dot matrix LCD
- > High accuracy up to 10,000e
- > Anti-vibration and anti-surge design
- > Easy to operation with big LCD display
- > Multi interface: RS232, RS485, Ethernet, etc.
- > Super anti-interference technology
- > Analog or digital working mode for choice

## Specifications

### POWER

100-240V (50-60Hz)

### PLATFORM SIZE

Width - 3m  
Length - 6 or 9m

### CAPACITY

30/50t

### ACCURACY

10kg/20kg

### UNITS

Kg, t

### OUTPUT

RS232  
RS485  
RJ45 (optional)  
SD card (optional)

### COMMUNICATION

Continuous  
Print  
Modbus-RTU  
Modbus-TCP  
Ethernet - optional

## Option



MDS | MDSS remote display

### Indicator/load-cell



K3000



M36i

## Models

Part No.	410053	410054
Models	TSM306	TSM309
Capacity	30Ton	50Ton
Division	10kg	20kg
Platform size	3x6m	3x9m