



NT Specifications

- Standard RS232 interface <
- Compact and fashion design <
- Epson* M-150II printing components <
- Independent power switch <
- Mounting sockets on bottom <
- Using for wall mounted <
- Paper width up to 57.5mm <
- Stable printing of 500,000 lines <

Technical Data

Power DC 5V 1.5-2.0A	Printing Width 16 24 40 ASCII letters/Second
Print Head Epson M-150II	Interface RS232
Ribbon Cartridge ERC-05/09	Operating Temperature 0°C - 40°C
Paper Width 44.5 57.5mm Outer	Dimension 123 x 165 x 66mm
Paper Roll Outer Φ ≤ 50mm, Φ 10mm ≤ Inner ≤ Φ 12mm	Weight 150 - 380g
Printing Speed 1.0 0.7 0.4 ASCII Line/Second	



P76 Specifications

- Faster and more reliable <
- Drop-in paper loading <
- Support two color printing (**black and purple**) <
- Widely used in cash register, banking, POS etc <
- Two type of paper rolls - 76mm or 57mm <
- Easy to operate and maintain <
- 1 original and 1 copy printing <
- Stable printing up to 5,000,000 lines <

Technical Data

Power DC 24V±10% 2A	Feeding Speed 80mm/second
Ribbon Cartridge ERC-39 Black or Purple	Interface RS232 Parallel Ethernet USB RJ-11
Paper Width 76mm / 57mm	Operating Temperature 0°C - 50°C
Paper Roll Outer Φ ≤ 83mm, Inner Φ ≤ 10+2mm Thickness: 0.05-0.08mm (total ≤ 0.2mm)	Dimension 248 x 160 x 142mm
Printing Speed 76mm - 4.4lines/second 57mm - 5.6lines/second	Weight 1.8kg

Models

Part No.	140063	140064
Models	NT	POS
U.P.(USD)	\$380.00	\$420.00
Paper	44.5 57.5mm	57 76mm