



### Specifications

- > Touch operation
- > New and fasion design
- > IP53 protection, no worry for wet environment, such as kitchen, food process line, etc.
- > High speed of 300mm/s
- > Long printing life of 100km
- > Easy operation and maintain.
- > Multi interfaces

### Technical Data

<b>Power</b> DC 24V±10% 2A	<b>Interface</b> RS232 Ethernet USB RJ-11 (24V cash box) Bluetooth (optional) WiFi (optional)
<b>Resolution</b> 8dots/mm (203dpi)	<b>Operating Temperature</b> 0°C - 50°C
<b>Paper Width</b> 80mm ± 0.5mm	<b>Dimension</b> 197 x 145 x 147mm
<b>Paper Roll</b> Thermal paper Ø80mm (max)	<b>Weight</b> 1.8kg
<b>Printing Speed</b> 300mm/s (max)	

### Specifications

- > Classic design
- > Thermal printing direct
- > 57mm paper width
- > Drop-in paper load
- > RS232 serial interface
- > Bluetooth connecting work together with X1, X3 X5, X6, X8, CF, K7, K7s with Bluetooth output.
- > Long working life of 100km print



### Technical Data

<b>Power</b> DC 12V, 2A	<b>Interface</b> Serial Parallel USB RJ-11 (12V 24V cash box) Bluetooth
<b>Resolution</b> 8dots/mm (384dots/line)	<b>Operating Temperature</b> 5°C - 50°C
<b>Paper Width</b> 57.5mm ± 0.5mm	<b>Dimension</b> 210 x 135 x 130mm
<b>Paper Roll</b> Thermal paper Ø83mm (max)	<b>Weight</b> 1kg
<b>Printing Speed</b> 90mm/s	



### Models

Part No.	140065	140066	140067
Models	P902	P58R	P58B
U.P.(USD)	\$380.00	\$180.00	\$260.00
Interface	RS232   USB	RS232   USB	RS232   Bluetooth

