



Specifications

- > Touch operation
- > New and fasion design
- > IP53 protection, no worry for wet environment, such as kitchen, food process line, etc.
- > High speed of 300mm/s
- > Long printing life of 100km
- > Easy operation and maintain.
- > Multi interfaces

Technical Data

Power DC 24V±10% 2A	Interface RS232 Ethernet USB RJ-11 (24V cash box) Bluetooth (optional) WiFi (optional)
Resolution 8dots/mm (203dpi)	Operating Temperature 0°C - 50°C
Paper Width 80mm ± 0.5mm	Dimension 197 x 145 x 147mm
Paper Roll Thermal paper Ø80mm (max)	Weight 1.8kg
Printing Speed 300mm/s (max)	

Specifications

- > Classic design
- > Thermal printing direct
- > 57mm paper width
- > Drop-in paper load
- > RS232 serial interface
- > Bluetooth connecting work together with X1, X3 X5, X6, X8, CF, K7, K7s with Bluetooth output.
- > Long working life of 100km print



Technical Data

Power DC 12V, 2A	Interface Serial Parallel USB RJ-11 (12V 24V cash box) Bluetooth
Resolution 8dots/mm (384dots/line)	Operating Temperature 5°C - 50°C
Paper Width 57.5mm ± 0.5mm	Dimension 210 x 135 x 130mm
Paper Roll Thermal paper Ø83mm (max)	Weight 1kg
Printing Speed 90mm/s	



Models

Part No.	140065	140066	140067
Models	P902	P58R	P58B
U.P.(USD)	\$380.00	\$180.00	\$260.00
Interface	RS232 USB	RS232 USB	RS232 Bluetooth

