



Specifications

- > Aluminum alloy housing
- > Super bright dot matrix LED display
- > Full height- 12cm
- > Half height - 6cm
- > Automatic detecting protocols
- > For all HIWEIGH X serial indicators
- > Suitable for many popular indicators: Moorrange*, Mettler Toledo*, Vishay*, Sartorius*, Flintec*, Ohaus*, etc.
- > Real time display (preset)
- > 20 Message display (31 characters)
- > Optional wireless connection with RS232-BOX
- > RD Driver software for easy setting
- > Customized protocol optional

*All those product names, logos, brands and other trademarks featured or referred to within this catalog are the property of their respective trademark holders.



RBOX

DDS

Power
100-240V 50/60Hz
-5V1.5Ah
-7.5-12V500mA

Power Consumption
1000mA - 5V power
200mA - 7.5-12V power

Display
18 groups (8x8)
height = 12cm (full) / 6cm (half)

Serial Input
RS232

Operating Temperature
-10°C - 40°C
≤85% non-condensing

Storage Temperature
-25°C - 55°C

Protection
IP54

Approval
CE

Dimensions:
700*158*43mm

Weight
2.5 kg

Specifications

- > Aluminum alloy housing
- > 3" bright LED display
- > Automatic detecting protocols
- > For all HIWEIGH X serial indicators
- > Suitable for many popular indicators: Moorrange*, Mettler Toledo*, Vishay*, Sartorius*, Flintec*, Ohaus*, etc.
- > Two status light setup (preset)
- > Optional wireless connection with RS232-BOX
- > Customized protocol optional

*All those product names, logos, brands and other trademarks featured or referred to within this catalog are the property of their respective trademark holders.



RBOX

RDS

Power
100-240V 50/60Hz
-13.4V - 14.4V

Display
3" LED

Serial Input
RS232

Operating Temperature
-10°C - 40°C
≤85% non-condensing

Storage Temperature
-25°C - 55°C

Protection
IP54

Approval
CE

Dimensions:
480*110*40mm

Weight
2.8 kg

Models

Part No.	140010	140011	140061
Models	DDS	RDS	RBOX
U.P.(USD)	\$528.00	\$180.00	\$260.00
Display	5"Dot Matrix	3"LED	-
Housing	Aluminum	Aluminum	-
IP Class	IP54	IP54	-