



### Technical Data

|   |  |
|---|--|
| <b>Power</b><br>DC 24V 2.5A                       | <b>Barcode</b><br>Code 39, Code 93, Code 128, EAN8, EAN8/13, EAN13, UCC/EAN128, UPC-A, UPC-E, etc. |
| <b>Resolution</b><br>8 dots/mm (203dpi)           | <b>Interface</b><br>USB (master/slave), Serial Ethernet (optional)                                 |
| <b>Mode</b><br>Thermal Transfer<br>Thermal Direct | <b>Operating Temperature</b><br>5°C - 45°C   |
| <b>Max. Paper Width</b><br>104mm (4.1")           | <b>Dimension</b><br>263.2 x 200 x 188.3mm  |
| <b>Max. Paper Length</b><br>3810mm (150")         | <b>Weight</b><br>2kg   |
| <b>Memory</b><br>8Mb SDRAM<br>4Mb Flash ROM       |  |



### T40.T40E Specifications

- Standard RS232 interface <
- Programmable label format <
- Bar code programmable <
- Multi weighing data collect <
- Suitable for almost all scales/indicators <
- Work for bar code reader also <
- 4MB Flash memory, 8MB SDRAM <
- 4 LED buttons indication <
- T40 with 64x128 LCD display <
- USB master and slave port <
- Serial port, Ethernet port (option) <
- Moveable reflective sensor <
- Easy paper and ribbon loading <



### Technical Data

|   |   |
|---|---|
| <b>Power</b><br>DC 12V800mA<br>7.4V2000mA Li-ion battery            | <b>Interface</b><br>PT2R:<br>RS232<br>USB<br>PT2B:<br>Bluetooth v2.1            |
| <b>Resolution</b><br>8 dots/mm, 384 dots/line                       | <b>Operating Temperature</b><br>-10°C - 50°C<br>5°C - 40°C (charge temperature) |
| <b>Paper Width</b><br>57.5mm ± 0.5mm                                | <b>Dimension</b><br>79 x 110 x 45mm   |
| <b>Effective Width</b><br>48mm                                      | <b>Weight</b><br>210g   |
| <b>Paper Roll</b><br>Dia 40mm outer (max.)<br>Dia 13mm inner (min.) |   |
| <b>Printing Speed</b><br>50-80mm/s                                  |   |

### PT2R.PT2B Specifications

- Portable and fashion design <
- With or without Li-ion battery for selection <
- Multi interface: RS232, USB, IR, etc. <
- PT2B with Bluetooth connect <
- Suitable for all X1 X3 X5 X6 X8 indicators and CF models with Bluetooth output <
- Auto sleep/wake up, power-saving mode <
- Thermal line printing directly <
- Work with 57mm paper <



### Models

| Part No.  | 140068            | 140069            | 140070          | 140071            |
|-----------|-------------------|-------------------|-----------------|-------------------|
| Models    | T40               | T40E              | PT2R            | PT2B              |
| U.P.(USD) | <b>\$1,840.00</b> | <b>\$1,160.00</b> | <b>\$232.00</b> | <b>\$272.00</b>   |
| Display   | LCD               | -                 | -               | -                 |
| Battery   | -                 | -                 | 7.4V2000mA      | 7.4V2000mA        |
| Interface | RS232   USB       | RS232   USB       | RS232   USB     | RS232   Bluetooth |