



### Specifications

- > Rugged ABS housing
- > Smart wireless RS232 connection
- > Use for:
  - Indicator - Remote display
  - Indicator - PC
  - Indicator - Printer
- > Baud rate can be chosen before delivery  
(according to the baud rate of the indicator it used)




### Technical Data

- Power**  
5V from the indicator  
5-9V from adaptor (optional)
- Interface**  
RS232
- Housing**  
Plastic

### Specifications

- > Aluminum housing
- > With rechargeable Li-ion 3.7V battery
- > Suitable for all analog load cells
- > Long working time of 270hrs more
- > Standby of 24 months
- > **Battery should be recharged every 5 months**
- > Long working distance of 150m
- > High accuracy till 1/10,000
- > 433MHz or 915MHz frequency
- > Drive 1-12 350Ω load cells
- > With LED indication lights



### Technical Data

- Power**  
4-5.5V DC adaptor
- Input**  
Transmitter < 12.9mV
- Excitation Voltage**  
3.3V - Transmitter  
5-15V - Receiver
- Output**  
Receiver - 3mV/V
- Accuracy**  
1/10,000
- Weight**  
0.8kg
- Frequency**  
433MHz or 915MHz
- Battery Life**  
> 270hrs
- Working Distance**  
150m
- Operating Temperature**  
-10°C - 45°C
- Storage Temperature**  
-25°C - 55°C



### Models

Part No.	140061	140062
Models	RBOX	WSW
<b>U.P.(USD)</b>	<b>\$260.00</b>	<b>\$540.00</b>
Type	RS232-RS232	PLATFORM-INDICATOR