



TechnicalData

Power AC 100-120V 50/60Hz, 0.5A AC 200-240V 50/60Hz, 0.5A	Interface: RS232 RJ45	Work Temp -10 - 40°C 20-90% RH
Capacity 6/15kg 15/30kg	Units kg/lb	Storage Temp -20 - 50°C 10-95% RH
Division 2/5g 5/10g	Label Size L: 25-48mm W: 30-58mm	Dimension 360x440x175/490mm
PLU 10,000	Printing Speed >50mm/s	Weight 8.5kg
Hotkeys 112*2	Printing Width 56mm (max)	
Display LCD 320*240	Paper Roll W: 58mm (max) Outer dia: 80mm (max) Internal dia: 40mm (min)	
S.S Pan Size 345 x 260mm		



Features

- 10,000 PLU storage <
- 224 (112*2) hotkeys of PLU <
- Different operation types < *weighing, fixed price, etc.*
- Print and barcode formats editable <
- Discounts in percentage or coupon <
- Additional or other extra charge <
- Automatic printing support <
- Reprint function <
- Zero/Tare function <
- Powerful network communications < *Programm setting, multiple-scales network back-office management via RS-232 or Ethernet*
- Easy programming of PLU/Barcode, etc. <
- Aluminum load cell supporter <
- Easy replacement of label roll <
- 4" TFT-LCD display (320*240) <
- RS232 and RJ45 interface <
- Cashbox-L - 410x420x100mm <
- Cashbox-S - 336x368x80mm <
- B-Reader - Barcode reader <

Models

Part No.	100914	100915	155002	155003	155004
Models	PCP15	PCP30	CASHBOX-S	CASHBOX-L	B-READER
U.P.(USD)	\$1,000.00	\$1,000.00	\$88.00	\$112.00	\$100.00
Capacity	6/15kg	15/30kg	-	-	-
Division	2/5g	5/10g	-	-	-
Overall Size	360 (W) x 440 (D) x 175/490mm (H)				
Weight	8.5kg				