

VALUE EACH GRAM
HiWEIGH
SERIES K7



SPECIFICATIONS

Display	Backlit FSTN LCD display
Units	kg / lb / g / oz
Output	2*RS232--K7, K7A, K7S 1*RS232--K7P
Display Resolution	1/3,000-1/30,000
A/D Resolution	1,000,000
A/D Rate	10 times/second
Operating Temperature	-10 °C - 40 °C

MODELS

Model	Part No.
K7	101007
K7A	101008
K7S IP54	101009
K7S IP65	101010
K7P	101011

OPTIONAL

Accessories	Part No.
Relay 4 output	109003
Bluetooth	109004
Bluetooth-(With app)	109005
RS485	109006
4-20mA	109007
Ethernet	109012
WiFi	109017



FUNCTIONS

- Continuous, print or Modbus output--K7, K7A, K7S
- Checkweigh
- Counting
- Accumulation (up to 2000 records)
- Animal weighing
- Hold
- x10 accuracy
- Percentage weighing
- Postive/negative weighing
- Minus weighing
- Manual and auto tare
- Multi setpoints configuration

FEATURES

- 37mm backlit FSTN LCD display
The best full view angle LCD makes it read clearly anywhere and anytime.
- Default with double RS232 interface
Which makes it work with printer, remote display or other device simultaneously.
- The K7 family indicators are widely used for most weighing needs.

EXCITATION

Analog Input Signal

±10mV

Power

100-240V AC

6V4Ah Rechargeable Battery-K7/K7A

6V2.8Ah Rechargeable Battery-K7S/K7P

Load cell

1-4*350Ω

1-8*700Ω

K7
IP67

ENCLOSURE

PBT

PACK SIZE

1190*720*160mm (8pcs)

WEIGHT

21.2kg(8pcs)



K7A
IP54

ENCLOSURE


PBT

PACK SIZE

480*590*600mm (15pcs)

WEIGHT

28kg(15pcs)



K7S
IP65

ENCLOSURE

SUS304 st

PACK SIZE

480*590*600mm (12pcs)

WEIGHT

27kg(12pcs)

K7P
IP54

ENCLOSURE

SUS304 stainless steel

PACK SIZE

540*470*400mm (5pcs)

WEIGHT

18.5kg(5pcs)

K7P PRINTER

- > Label printer with edit APP
- > Printer works with receipt or label, automatic detection
- > Paper width: 57.5(+/-0.5)mm
- > Printing width: 48mm (384dots)
- > The resolution is 203DPI, 8 dots/mm
- > Paper roll diameter: 80mm (Max)
- > Working life of print head: 50km