

VALUE EACH GRAM

HiWEIGH

K3000 (D)



SPECIFICATIONS

Display	240*128mm LCD display
Units	kg / ton / lb
Output	1*RS232 and 1*RS485
Display Resolution	1/3,000-1/60,000
A/D Rate	120 times/second
Operating Temperature	0 °C - 40 °C
Enclosure	SUS304 stainless steel

FUNCTIONS


- Auto zero range
- Programmable date to lock
- Continuous and stable output
- Multi communication protocols

MODELS

Model	Part No.
K3000	102002
K3000D	102003

OPTIONAL

Accessories	Part No.
ScaleX operating system	109011
Ethernet	109012
Multi-range	109013
Keyboard connecting	109014



FEATURES

IP65

- Default with 1*RS232 and 1*RS485
The RS232 with adjustable baud rate.
- Fast response
- 26 function keys
Easy to operate.
- All communication interface
isolation and Anti-surge design
It is more suitable for tank trucks and so on.
- Analog version – K3000:
*Drive up to 12*3500Ω load cells*
- Digital version – K3000D:
Working with HBM AWT* FLINTEC*
CAS* ZEMIC* and more digital load cells*
**All brands and logo belong to the owner.*

EXCITATION

Power

100-240V AC

Load cell

12*3500Ω--K3000

Digital load cells--K3000D

PACK SIZE

330*260*210cm (1pcs)

WEIGHT

3kg (1pcs)