

VALUE EACH GRAM
HiWEIGH
X6



SPECIFICATIONS

Display	Green LED
Units	kg / ton
Output	RS232*1
Display Resolution	1/3,000-1/30,000
A/D Resolution	1,500,000
A/D Rate	60 times/second
Operating Temperature	0 °C - 45 °C
Enclosure	Stainless steel

FUNCTIONS

- Auto zero range
- Programmable date to lock
- Lock with 130% F.S overloading
- Manual or automatic printout
- 200 vehicle numbers and tares
- 2000 weighing records and 10 unit prices
- Daily, monthly statistics reports
(By time, vehicle or goods numbers)
- Selectable digital filter
- Continuous and stable output

MODELS

Model	Part No.
X6	102001

OPTIONAL

Accessories	Part No.
Bluetooth	109004
Ethernet/WiFi	109006
ScaleX operating system	109013



FEATURES

IP54

- Default with RS232 interface
 - > Which makes it work with printer, remote display or other devices.
 - > The RS232 with continuous or print output.
 - > The RS232 with adjustable baud rate.
- 28 function keys
 - > Easy to operate
 - > Parallel printer port, work with dot matrix printers, like Panasonic KX-P1131+, etc.

EXCITATION

Power

100-240V AC

6V4Ah Rechargeable battery

Load cell

1-12*350Ω

1-24*750Ω

PACK SIZE

420*590*600mm (4pcs)

WEIGHT

21kg(4pcs)

